



Filament lamp, 24 V, BA 9s, 2.0W

**Part no.** A22-GL24  
**Catalog No.** 261360  
**Alternate Catalog No.** A22-GL24  
**EL-Nummer (Norway)** 4355669

### Delivery program

Accessories			General accessories
Basic function accessories			Filament bulbs
			high-grade versions from selected manufacturers
Type			24 V/2.0 W
Lifespan to EN 60064 at $t_a = +25\text{ °C}$	$t_{\text{mean}}$ (AC)	h	5000
Connection to SmartWire-DT			no

### Technical data

#### General

Ambient temperature			
Open		°C	-25 - +70

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

### Technical data ETIM 7.0

Lamps (EG000028) / Indication- and signalling lamp (EC000399)			
Electric engineering, automation, process control engineering / Lighting installation, device / Light medium / Indication- and signal lamp (ecl@ss10.0.1-27-11-06-31 [AKE242014])			
Lamp power		W	
Lamp voltage		V	24 - 24
Luminous flux		lm	0
Socket			BA9s
Technology			LED
Lamp shape			Pear-shape
Halogen			No
Krypton			No
Xenon			No
Colour			None
Colour temperature		K	0
Diameter		mm	0
Total length		mm	0
Suitable for torches			No
Suitable for pointer			Yes
Suitable for round flashing luminaire			
Nominal current		mA	83
Average nominal lifespan		h	5000
Energy efficiency class			

### Additional product information (links)

<b>IL04716002Z (AWA1160-1745) RMQ-Titan System</b>	
IL04716002Z (AWA1160-1745) RMQ-Titan System	<a href="ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716002Z2018_10.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716002Z2018_10.pdf</a>