

Box terminal, 3p, bottom up to 630A



**Part no.** +NZM3-XKCU  
**262245**  
**EL Number** 4315557  
**(Norway)**

General specifications		
Product name		Eaton Moeller series NZM - Molded Case Circuit Breaker
Part no.		+NZM3-XKCU
EAN		4015082622459
Product Length/Depth		120.5 millimetre
Product height		275 millimetre
Product width		140 millimetre
Product weight		0.134 kilogram
Compliances		UL/CSA IEC RoHS conform
Certifications		UL (Category Control Number DIHS) UL listed UL489 CSA (File No. 22086) IEC60947 CSA certified UL (File No. E31593) CE marking CSA-C22.2 No. 5-09
Product Tradename		NZM
Product Type		Molded Case Circuit Breaker
Product Sub Type		None
Delivery program		
Type		Accessory Box terminal Terminal
Number of poles		Three-pole
Amperage Rating		≤ 630 A
Frame		NZM3
Suitable for		Copper cable Three-pole
Used with		NZM3(-4), PN3(-4), N(S)3(-4)
Technical Data - Mechanical		
Mounting position		Fitted at the bottom
Technical Data - Mechanical - Terminals		
Terminal capacity (stranded cable)		16 mm <sup>2</sup> - 120 mm <sup>2</sup> (2x) 2 - 500 AWG/kcmil (1x) 35 mm <sup>2</sup> - 240 mm <sup>2</sup> (1x)
Terminal capacity (copper strip)		630 A: 10 segments of 24 mm x 1 mm + 5 segments of 24 mm x 1 mm or 8 segments of 24 mm x 1 mm (2x) Max. 500 A: 6 segments of 16 mm x 0.8 mm - 10 segments of 24 mm x 1 mm or 11 segments of 21 mm x 1 mm
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>Additional information</b>			
Model			Other

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss13-27-37-04-24 [ACN957016])			
Suitable for number of poles			3
Model			Other