

Fuse disconnectors, 3pole+N, 10 x 38



**Part no.**                    **Z-SHL/3N**  
**263887**

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-SHL/3N
EAN		4015082638870
Product Length/Depth		80 millimetre
Product height		74 millimetre
Product width		52.5 millimetre
Product weight		0.245 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Actuator position		Front side
Actuator type		Other
Cable entry type		Other
Conditioned rated short-circuit current Iq		10 kA
Degree of protection (front side)		IP20
Electrical connection type of main circuit		Screw connection
Number of poles		Four-pole
Power rating at AC-23, 400 V		0 kW
Rated conditional short-circuit current (Iq)		10 kA
Rated operating voltage (Ue) at AC - max		400 V
Rated operation power at AC-23, 400 V		0 kW
Rated short-time withstand current (Icw)		0 kA
Rated uninterrupted current (Iu)		32 A
Suitable for fuses		Shape C1-C3

**Technical data ETIM 9.0**

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecl@ss13-27-37-14-01 [AKF058018])		
Version as main switch		No
Version as safety switch		No
Max. rated operation voltage Ue AC	V	400
Rated permanent current Iu	A	32
Rated operation power at AC-23, 400 V	kW	0
Conditioned rated short-circuit current Iq	kA	10
Rated short-time withstand current Icw	kA	0
Suitable for fuses		Shape C1-C3
Number of poles		4
With error protection		No
Type of electrical connection of main circuit		Screw connection
Cable entry		Other
Equipped with connectors		No
Suitable for floor mounting		No

Suitable for front mounting			No
Suitable for busbar mounting			No
Type of control element			Other
Position control element			Front side
Motor drive optional			No
Motor drive integrated			No
Version as emergency stop installation			No
Degree of protection (IP), front side			IP20