

Circuit-breaker, 4p, 1250A



Part no. **NZMN4-4-AE1250**
265915

General specifications	
Product name	Eaton Moeller series NZM molded case circuit breaker electronic
Part no.	NZMN4-4-AE1250
EAN	4015082659158
Product Length/Depth	401 millimetre
Product height	207 millimetre
Product width	280 millimetre
Product weight	25.217 kilogram
Compliances	RoHS conform
Certifications	IEC IEC/EN 60947
Product Tradename	NZM
Product Type	Molded case circuit breaker
Product Sub Type	Electronic
Delivery program	
Application	Use in unearthed supply systems at 525 V
Type	Circuit breaker
Circuit breaker frame type	NZM4
Number of poles	Four-pole
Amperage Rating	1250 A
Release system	Electronic release
Features	Motor drive optional Protection unit
Special features	Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I _{cn}) Rated current = rated uninterrupted current: 1250 A Set value in neutral conductor is synchronous with set value I _r of main pole. R.m.s. value measurement and "thermal memory"
Technical Data - Electrical	
Voltage rating	690 V - 690 V
Rated insulation voltage (U _i)	1000 V AC
Rated impulse withstand voltage (U _{imp}) at auxiliary contacts	6000 V
Rated impulse withstand voltage (U _{imp}) at main contacts	8000 V
Current rating of neutral conductor	200% of phase conductor
Rated short-time withstand current (t = 0.3 s)	19.2 kA
Rated short-time withstand current (t = 1 s)	19.2 kA
Instantaneous current setting (I _i) - min	2500 A
Instantaneous current setting (I _i) - max	15000 A
Overload current setting (I _r)	630 A - 1250 A
Overload current setting (I _r) - min	630 A
Overload current setting (I _r) - max	1250 A
Short delay current setting (I _{sd}) - min	0 A
Short delay current setting (I _{sd}) - max	0 A
Short-circuit release non-delayed setting - min	2500 A
Short-circuit release non-delayed setting - max	15000 A
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 230 V, 50/60 Hz	37 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 400/415 V, 50/60 Hz	37 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 440 V, 50/60 Hz	26 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 525 V, 50/60 Hz	19 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 690 V, 50/60 Hz	15 kA
Rated short-circuit making capacity I _{cm} at 240 V, 50/60 Hz	105 kA

Rated short-circuit making capacity I _{cm} at 400/415 V, 50/60 Hz		105 kA
Rated short-circuit making capacity I _{cm} at 440 V, 50/60 Hz		74 kA
Rated short-circuit making capacity I _{cm} at 525 V, 50/60 Hz		53 kA
Rated short-circuit making capacity I _{cm} at 690 V, 50/60 Hz		40 kA
Short-circuit total breaktime		< 25 ms (≤ 415 V); < 35 ms (> 415 V)
Electrical connection type of main circuit		Screw connection
Isolation		300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts)
Number of operations per hour - max		60
Handle type		Rocker lever
Utilization category		A (IEC/EN 60947-2)
Overvoltage category		III
Pollution degree		3
Lifespan, electrical		2000 operations at 415 V AC-3 3000 operations at 400 V AC-1 3000 operations at 415 V AC-1 1000 operations at 690 V AC-3 2000 operations at 690 V AC-1 2000 operations at 400 V AC-3
Direction of incoming supply		As required
Technical Data - Mechanical		
Mounting Method		Fixed Built-in device fixed built-in technique
Degree of protection		IP20 (basic degree of protection, in the operating controls area) IP20
Degree of protection (IP), front side		IP40 (with insulating surround) IP66 (with door coupling rotary handle)
Degree of protection (terminations)		IP00 (terminations, phase isolator and strip terminal) IP10 (tunnel terminal)
Protection against direct contact		Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
Shock resistance		15 g (half-sinusoidal shock 11 ms)
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Position of connection for main current circuit		Front side
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Special features		Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I _{cn}) Rated current = rated uninterrupted current: 1250 A Set value in neutral conductor is synchronous with set value I _r of main pole. R.m.s. value measurement and "thermal memory"
Lifespan, mechanical		10000 operations
Technical Data - Mechanical - Terminals		
Standard terminals		Screw terminal
Optional terminals		Connection on rear. Strip terminal. Tunnel terminal
Terminal capacity (control cable)		0.75 mm ² - 2.5 mm ² (1x) 0.75 mm ² - 1.5 mm ² (2x)
Terminal capacity (aluminum solid conductor/cable)		240 mm ² (2x) at rear-side width extension 50 mm ² (4x) at rear-side 2-hole module plate 185 mm ² - 240 mm ² (1x) at rear-side 1-hole module plate 70 mm ² - 185 mm ² (2x) at rear-side 1-hole module plate 70 mm ² - 240 mm ² (6x) at rear-side width extension
Terminal capacity (aluminum stranded conductor/cable)		50 mm ² - 240 mm ² (4x) at 4-hole tunnel terminal
Terminal capacity (copper busbar)		Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate Max. 80 mm x 10 mm (2x) at rear-side width extension M10 at rear-side screw connection Max. 50 mm x 10 mm (2x) direct at switch rear-side connection Min. 25 mm x 5 mm at rear-side 1-hole module plate Min. 60 mm x 10 mm at rear-side width extension 50 mm x 10 mm (2x) at rear-side 2-hole module plate Min. 25 mm x 5 mm direct at switch rear-side connection
Terminal capacity (copper solid conductor/cable)		95 mm ² - 240 mm ² (6x) at rear-side width extension 50 mm ² - 240 mm ² (4x) at 4-hole tunnel terminal 95 mm ² - 300 mm ² (2x) at rear-side 1-hole module plate 300 mm ² (4x) at rear-side width extension 120 mm ² - 300 mm ² (1x) at rear-side 1-hole module plate 95 mm ² - 185 mm ² (2x) at rear-side 2-hole module plate 35 mm ² - 185 mm ² (4x) at rear-side 2-hole module plate

Terminal capacity (copper stranded conductor/cable)		120 mm ² - 185 mm ² (1x) direct at switch rear-side connection 50 mm ² - 185 mm ² (4x) direct at switch rear-side connection
Terminal capacity (copper strip)		Max. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched) Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor terminal Min. 5 segments of 25 mm x 1 mm at rear-side connection (punched) 10 segments of 50 mm x 1 mm (2x) at 1-hole module plate 10 segments of 80 mm x 1 mm (2x) at rear-side width extension
Design verification as per IEC/EN 61439 - technical data		
Rated operational current for specified heat dissipation (I _n)		1250 A
Equipment heat dissipation, current-dependent		173.44 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		-40 °C
Ambient storage temperature - max		70 °C
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information		
Functions		System and cable protection

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018])		
Rated permanent current I _u	A	1250
Rated voltage	V	690 - 690
Rated short-circuit breaking capacity I _{cu} at 400 V, 50 Hz	kA	37
Overload release current setting	A	630 - 1250
Adjustment range short-term delayed short-circuit release	A	0 - 0
Adjustment range undelayed short-circuit release	A	2500 - 15000
Power loss	W	
Device construction		Built-in device fixed built-in technique
Integrated earth fault protection		No
Type of electrical connection of main circuit		Screw connection
Suitable for DIN rail (top hat rail) mounting		No

DIN rail (top hat rail) mounting optional		No
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		0
With switched-off indicator		No
With integrated under voltage release		No
Number of poles		4
Position of connection for main current circuit		Front side
Type of control element		Rocker lever
Complete device with protection unit		Yes
Motor drive integrated		No
Motor drive optional		Yes
Degree of protection (IP)		IP20