



**Busbar, isolated, 63A, 3p, 3Mod**



Powering Business Worldwide™

**Part no. Z-GV-10/3P-3TE**  
**Catalog No. 271060**

Similar to illustration

**Technical data ETIM 7.0**

|  |  |                 |      |
|--|--|-----------------|------|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215)   |  |                 |      |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss10.0.1-27-37-13-06 [ACN992011]) |  |                 |      |
| Number of phases   |  |                 | 3    |
| Number of poles  |  |                 | 3    |
| Suitable for number of devices   |  |                 | 0    |
| Pitch dimensions   |  | mm              | 0    |
| Cross section  |  | mm <sup>2</sup> | 10   |
| Length   |  | mm              | 1000 |
| Number of modular spacings   |  |                 | 3    |
| Rated permanent current I <sub>u</sub>   |  | A               | 63   |
| Type of electric connection  |  |                 | Fork |
| Insulated  |  |                 | Yes  |
| Rated surge voltage  |  | kV              | 4    |
| Conditioned rated short-circuit current I <sub>q</sub>   |  | kA              | 0    |
| Max. rated operation voltage U <sub>e</sub>  |  | V               | 500  |
| Rated short-time withstand current I <sub>cw</sub>   |  | kA              | 0    |
| Suitable for devices with N-busbar   |  |                 | No   |
| Suitable for devices with auxiliary switch   |  |                 | No   |