

Varistor suppressor circuit, 130 - 240 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200



**Part no.** DILM95-XSPV240

281218

**EL Number**

4110358

**(Norway)**

General specifications	
Product name	Eaton Moeller® series DILM varistor suppressor circuit
Part no.	DILM95-XSPV240
EAN	4015082812188
Product Length/Depth	43 millimetre
Product height	25 millimetre
Product width	9 millimetre
Product weight	0.005 kilogram
Certifications	CSA UL File No.: E29184 CSA Class No.: 3211-07 CE UL Category Control No.: NKCR2, NKCR8 IEC/EN 60947-4-1 UL Recognized CSA-C22.2 No. 14-05 CSA File No.: 256465 UL 508
Product Tradename	DILM
Product Type	Accessory
Product Sub Type	Varistor suppressor circuit
Catalog Notes	With DC operated contactors and with DILM115 and DILM150 the suppressor is integrated.
Features & Functions	
Functions	Varistor (voltage-sensitive resistor)
General information	
Product category	Accessories
Voltage type	AC
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	60 °C
Magnet system	
Rated control supply voltage (Us) at AC, 50 Hz - min	130 V
Rated control supply voltage (Us) at AC, 50 Hz - max	240 V
Rated control supply voltage (Us) at AC, 60 Hz - min	130 V
Rated control supply voltage (Us) at AC, 60 Hz - max	240 V
Rated control supply voltage (Us) at DC - min	0 V
Rated control supply voltage (Us) at DC - max	0 V
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdis	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Surge protection module (EC000683)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Component for protective circuit (ecl@ss13-27-37-10-10 [AKF019018])			
Function			Varistor (voltage-sensitive resistor)
Voltage type (operating voltage)			AC
Operating voltage AC 50 Hz		V	230 - 690
Operating voltage AC 60 Hz		V	230 - 690
Operating voltage DC		V	0 - 0
With LED indication			No