

**Insulated enclosure, E-PKZ0, H x W x D = 129 x 90 x 115 mm, flush-mounted**

**Part no. E-PKZ01**

**281633**

**EL Number  
(Norway) 4365004**

<b>General specifications</b>		
Product name		Eaton Moeller® series E-PKZ0 Accessory Insulated enclosure
Part no.		E-PKZ01
EAN		4015082816339
Product Length/Depth		115 millimetre
Product height		129 millimetre
Product width		90 millimetre
Product weight		0.22 kilogram
Certifications		IEC/EN 60947-4-1 CSA UL File No.: E36332 CE UL Category Control No.: NLRV UL CSA-C22.2 No. 14 UL 508 CSA File No.: 165628 CSA Class No.: 3211-05
Product Tradename		E-PKZ0
Product Type		Accessory
Product Sub Type		Insulated enclosure
<b>Features &amp; Functions</b>		
Enclosure material		Plastic
Fitted with:		PE(N) terminal
<b>General information</b>		
Degree of protection		IP40 NEMA Other
Degree of protection (front side)		IP40
Model		Built-in
Product category		Accessories
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		40 °C
<b>Design verification</b>		
Equipment heat dissipation, current-dependent P <sub>vid</sub>		0 W
Heat dissipation capacity P <sub>diss</sub>		0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>		0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		0 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss13-27-37-13-01 [AKN343019])		
Housing material		Plastic
Width	mm	90
Height	mm	129
Depth	mm	115
With transparent cover		No
Suitable for emergency stop		No
Model		Built-in
Degree of protection (IP)		IP40
Degree of protection (NEMA)		Other