DATASHEET - BC-U-2/36-TW-ECO



ECO Compact distribution board, flush mounting, 2-rows, 18 MU, IP40

Powering Business Worldwide*

Part no. BC-U-2/36-TW-ECO Catalog No. 281711

Delivery program

Dontoly program			
Basic function			Basic device
Product function			Installation distribution boards
Product range			ECO DBO
Design			Flush mounted
Installation site			Indoor
Type of installation			Flush mounting
Door/Flap			White
Degree of Protection			IP40
Colour			White
Module rack			Single-rail
Shroud for protection against accidental contact			Plastic
Rows	Count		2
Module units per row			18
Description			IP40 Protection Class II Plastic housing white (RAL 9003)
Cable entries			Cable entry ribs on top and bottom
PE and N terminals design			Screw terminals
PE and N terminals	Number x cross- sectional area	mm ²	PE: 2 x (18 x 10) N: 2 x (18 x 10)
Equipment supplied			Basic device Device support rails Neutral-/protective conductor terminal

Technical data

General

Conordi			
Standards			EN 62208_x
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)			conform
Ambient temperature		°C	-20 - +70
Degree of Protection			IP40
Protection class			II (totally insulated)
Rated operational voltage	Ue	V AC	400
Rated frequency	f	Hz	50
Material characteristics			
Material			ABS (plastic)
Colour			white (RAL 9003)
Material properties			
Mechanical			
Impact resistance			IK05

Design verification as per IEC/EN 61439

IEC/EN 61439 design verification	
10.2 Strength of materials and parts	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects $ \frac{1}{2} \left(\frac{1}{2} \right) = \frac{1}{2} \left(\frac{1}{2} \right) \left($	850 °C; meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Not relevant to indoor installations.

10.2.5 Lifting	Does not apply to enclosures without lifting aids.
10.2.6 Mechanical impact	IK05
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES	IP40
10.4 Clearances and creepage distances	Is the panel builder's responsibility.
10.5 Protection against electric shock	Protection class 2, therefore not applicable.
10.6 Incorporation of switching devices and components	Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9 Insulation properties	
10.9.2 Power-frequency electric strength	U _i = 400 V AC
10.9.3 Impulse withstand voltage	3.75 kV
10.9.4 Testing of enclosures made of insulating material	Meets the product standard's requirements.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
10.13 Mechanical function	Meets the product standard's requirements.

Technical data ETIM 7.0

Distribution boards	(EG000023)	/ Small distribution board	(EC000214)
---------------------	------------	----------------------------	------------

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Small distribution board (ept@ss10.01-27-14-24-09 [ACN387011])

(ecl@ss10.0.1-27-14-24-09 [ACN387011])		
Mounting method		Flush mounted (plaster)
Number of rows		2
Width in number of modular spacings		18
Type of cover		Door
Cover model		Closed
Transparent cover/door		No
Material housing		Plastic
Height	mm	406
Width	mm	410
Depth	mm	105
Built-in depth	mm	70
Internal depth	mm	98
DIN-rail		Yes
With mounting plate		No
Extension possible		No
EMC-version		No
Colour		White
RAL-number		9003
Degree of protection (IP)		IP40
With lock		No
Type of closure		Other

Dimensions 60 mm (2.36") 380 mm (14.96") 46 mm (1.81") 346 mm (13.62") 409 mm (16.1")

Additional product information (links)

IL014002Z ECO compact distribution board	
IL014002Z ECO compact distribution board	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL014002ZU2014_02.pdf
Product overview (Web)	http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm