

**Busbar support 630A**

**Part no.**                    **BPZ-BBS-4/630**  
**289869**  
**EL Number**                **2473263**  
**(Norway)**

<b>General specifications</b>		
Product name		Eaton xEnergy Basic other accessory
Part no.		BPZ-BBS-4/630
EAN		4015082898694
Product Length/Depth		230 millimetre
Product height		55 millimetre
Product width		140 millimetre
Product weight		0.56 kilogram
Compliances		RoHS conform
Product Tradename		xEnergy Basic
Product Type		Accessories
Product Sub Type		Other
<b>Delivery program</b>		
Amperage rating		630 A
Number of poles		Four-pole
<b>Technical Data - Electrical</b>		
Current rating - max		630 A
Rated short-time withstand current (I <sub>cw</sub> )		23 kA
<b>Technical Data - Mechanical</b>		
Mounting method		Surface mounting Floor standing distribution board
Mounting position		Universal
Material		Plastic
Busbar distance		30 mm
Busbar height		10 mm
Busbar position		Bottom rear
Busbar thickness - max		30 mm
<b>Additional information</b>		
Functions		Additional equipment

**Technical data ETIM 9.0**

Energy distribution systems (EG000015) / Distributor assembly busbars (EC001896)		
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly busbars (ecl@ss13-27-40-06-10 [AC0383016])		
Height	mm	55
Width	mm	140
Depth	mm	230
With cover		No
Number of poles		4
Busbar distance	mm	30
Busbar height	mm	10
Busbar thickness	mm	30
Max. rated current	A	630
Short-circuit breaking capacity (I <sub>cw</sub> )	kA	23
Busbar position		Bottom rear