



**Eaton 5P 650i Rack1U**



Powering Business Worldwide™

**Part no.** Eaton 5P 650i Rack1U  
**Catalog No.** 5P650IR

## Delivery program

Product range		UPS
---------------	--	-----

## Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecl@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	160 - 294
Primary frequency	Hz	50 - 60
Number of phases primary		1
Output voltage	V	200 - 240
Secondary frequency	Hz	50 - 60
Output effective power	W	420
Output apparent power	VA	650
Type of interface		Other
Number of phases secondary		1
SNMP		Yes
Voltage type		AC
Height	mm	43.2
Width	mm	438
Depth	mm	364
Transition time for full load	min	2
Weight	kg	8.6
Network-management		Yes
USV- technology		Line-interactive
Construction type		482.6 mm (19 inch) device
Max. voltage distortion output (linear load)	%	0
Output power factor		0.6
Overall efficiency	%	96
Efficiency in eco-mode	%	96
Potential free switch contact		Yes
Auto shut down function		Yes
Input connection		C14
Number of output connections C13		4
Number of output connections C19		0
Number of output connections with protective contact (SCHUKO)		0
Number of output connections fixed connection		0