



Eaton 5S 1500i

**Part no.
Catalog No.**

**Eaton 5S 1500i
5S1500I**

Delivery program

Product range		UPS
---------------	--	-----

Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecl@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	175 - 275
Primary frequency	Hz	50 - 60
Number of phases primary		1
Output voltage	V	220 - 240
Secondary frequency	Hz	50 - 60
Output effective power	W	900
Output apparent power	VA	1500
Type of interface		USB
Number of phases secondary		1
SNMP		No
Voltage type		AC
Height	mm	250
Width	mm	87
Depth	mm	382
Transition time for full load	min	2
Weight	kg	11.08
Network-management		No
USV- technology		Line-interactive
Construction type		Free standing model
Max. voltage distortion output (linear load)	%	0
Output power factor		0.6
Overall efficiency	%	95
Efficiency in eco-mode	%	95
Potential free switch contact		No
Auto shut down function		Yes
Input connection		Protective contact (SCHUKO)
Number of output connections C13		8
Number of output connections C19		0
Number of output connections with protective contact (SCHUKO)		0
Number of output connections fixed connection		0