




Busbar assembly, 3p, in=250A

Part no. SE-RS-I44
Catalog No. 001890

EL-Nummer 2502016
(Norway)

Delivery program

			
Product range			xEnergy Safety Ci
Basic function			Prepared enclosures
Product function			Modular busbar system
Accessories			Busbar assemblies
Single unit/Complete unit			Modular system
Function			for fitting busbar mounting fuse bases 3 pole, for 250 A rated operational current
For use with			CI44...

Technical data ETIM 7.0

Energy distribution systems (EG000015) / Busbar support (EC001166)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar support (ecl@ss10.0.1-27-40-06-07 [AC0377011])			
Number of poles			3
Max. rated current		A	250
Busbar distance		mm	50

Additional product information (links)

Manufacturer's Declaration CI-RoHS	https://es-assets.eaton.com/DOCUMENTATION/PDF/2013-01-31_Ci_RoHS.pdf
Declaration of conformity	https://es-assets.eaton.com/DOCUMENTATION/PDF/ci_ce.pdf
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&RenderModelCertification=xEnergySafetyCi	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&model certification xEnergy Safety Ci
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&RenderModelCertification=xEnergySafetyCi	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&Save time – we assist you with expert pre-assembly
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&RenderModelCertification=xEnergySafetyCi	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&product information xEnergy Safety Ci
tool for calculating the power loss for switching device combinations	http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm
configurator - xEnergy family	http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/xEnergyMainSupport/index.htm