



**Notching tool**

**Part no.** BA/C-NZ-22  
**Catalog No.** 028144  
**Alternate Catalog No.** BA-C-NZ-22Q

**Delivery program**

Accessories			General accessories
Basic function accessories			Notching tool
			Punching tool to produce the cutout for the anti-rotation lug to IEC/EN 60947#5#1 St 37 sheet steel, max. 3 mm thick VA high-grade steel max. 1.5 mm thick,
Connection to SmartWire-DT			no
For use with			St 37 sheet steel, max. 3 mm thick VA high-grade steel max. 1.5 mm thick,
<b>Notes</b>			
Price cannot be discounted			

**Technical data**

**General**

Ambient temperature			
Open		°C	-25 - +70

**Design verification as per IEC/EN 61439**

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

**Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Accessories for control circuit devices (EC002024)			
Type of electrical accessory			Other
Type of mechanical accessory			Other

**Approvals**

North America Certification			UL/CSA certification not required
-----------------------------	--	--	-----------------------------------

**Assets (links)**

**Declaration of CE Conformity**

00003256

**Instruction Leaflets**

IL04716011Z2011\_02

**Additional product information (links)**

<b>IL04716011Z (AWA1160-2338) notching pliers</b>	
IL04716011Z (AWA1160-2338) notching pliers	<a href="ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716011Z2011_02.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716011Z2011_02.pdf</a>