



Busbar support, for CI enclosure 375mm, hxD=20x5(10, 15)mm

Part no. SH0635/4
 Catalog No. 060620

EL-Nummer 2502251
 (Norway)

Delivery program

Product range			xEnergy Safety Ci
Basic function			Prepared enclosures
Product function			Accessories for busbar enclosures
Accessories			Busbar support
Function			For use between two enclosures
Description			Component mounting possible on busbar Interval between busbar supports max. 375 mm
Interval between busbar centres		mm	50
Width		mm	375
Rated operational current	I_e	A	250 400 630
For use with			L1, L2, L3, PE, N, PEN: 20 x 5 L1, L2, L3: 20 x 10; PE, N, PEN: 20 x 5 L1, L2, L3: 20 x 10 + 20 x 5; PE, N, PEN: 20 x 10
For use with			CI48... CI45... CI44... CI43...

Technical data ETIM 7.0

Energy distribution systems (EG000015) / Busbar support (EC001166)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar support (ecl@ss10.0.1-27-40-06-07 [AC0377011])			
Number of poles			5
Max. rated current		A	630
Busbar distance		mm	50

Additional product information (links)

allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1&model%20certification%20xEnergy%20Safety%20Ci	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&...
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1&Save%20time%20-%20we%20assist%20you%20with%20expert%20pre-assembly	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&...
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1&product%20information%20xEnergy%20Safety%20Ci	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&...
tool for calculating the power loss for switching device combinations	http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm
configurator - xEnergy family	http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/xEnergyMainSupport/index.htm