## DATASHEET - V/EA/SVB-T0

Conversion kit on main switch, handle red yellow, for TO-/E-/Z



Part no.	
----------	--

V/EA/SVB-T0 062638

Product name	Eaton Moeller® series Accessory Insulated enclosure
Part no.	V/EA/SVB-T0
EAN	4015080626381
Product Length/Depth	50 millimetre
Product height	48 millimetre
Product width	48 millimetre
Product weight	0.07 kilogram
Certifications	UL/CSA certification not required
Product Tradename	None
Product Type	Accessory
Product Sub Type	Insulated enclosure
Color	Red Yellow
Fitted with:	Padlocking feature
Functions	For converting flush mounting switch T/E into flush mounting main switch T/
	EA/SVB
	Emergency switching off function Emergency stop function
	For converting rear mounting switch T…/Z (with FS908 front plate) into interlocke rear mounting main switch T…/V/SVB
Accessory/spare part type	Mounting set
Suitable for	Only for main switch
Switching angle	90 °
Туре	Assembly kit
	Main switch assembly kit With red rotary handle and yellow locking ring
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	50 °C
· · · · · · · · · · · · · · · · · · ·	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## **Technical data ETIM 8.0**

Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])

Type of accessory/spare part	Mounting set
Accessory	Yes
Spare part	No