



Support strut to base SS, L=505mm

**Part no.** STR50-ID  
**Catalog No.** 072493

### Delivery program

Product range			Ci insulated enclosures
Basic function			Distribution board assembly
Product function			Accessories
Accessories			Support struts
Function			For floor-standing distribution boards to support the vertical section on the floor
For use with			For plinth height 50 cm
<b>Notes</b>			
Additional accessories →#095750			
<b>Notes</b> For plinth height 50 cm			

### Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Mounting accessories (switchgear cabinet) (EC002625)			
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Elements for switching cabinet, housing, rack / Mounting accessories (electrical cabinet) (ecl@ss10.0.1-27-18-28-07 [AKE481013])			
Type of accessory			Other
Material			Stainless steel
Width		mm	505
Height		mm	25
Depth		mm	16

### Additional product information (links)

allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1&model%20certification%20xEnergy%20Safety%20Ci	<a href="http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;model%20certification%20xEnergy%20Safety%20Ci">http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;model certification xEnergy Safety Ci</a>
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1&Save%20time%20-%20we%20assist%20you%20with%20expert%20pre-assembly	<a href="http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;Save%20time%20-%20we%20assist%20you%20with%20expert%20pre-assembly">http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;Save time – we assist you with expert pre-assembly</a>
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1&product%20information%20xEnergy%20Safety%20Ci	<a href="http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;product%20information%20xEnergy%20Safety%20Ci">http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;product information xEnergy Safety Ci</a>
tool for calculating the power loss for switching device combinations	<a href="http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm">http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm</a>
configurator - xEnergy family	<a href="http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/xEnergyMainSupport/index.htm">http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/xEnergyMainSupport/index.htm</a>