

**Undervoltage release PKZ0(4), PKE, AC, 230 V 50 Hz, Screw terminals,
When ordered with basic unit**



**Part no. +U-PKZ0(230V50HZ)
 073250**

Product name	Eaton Moeller® series U-PKZ0 Accessory Undervoltage Release
Part no.	+U-PKZ0(230V50HZ)
EAN	4015080732501
Product Length/Depth	68 millimetre
Product height	90 millimetre
Product width	24 millimetre
Product weight	0.129 kilogram
Certifications	UL Listed CSA-C22.2 No. 14 IEC 60947-4-1 CSA certified UL Category Control No.: NLRV UL 508 CSA Class No.: 3211-05 CSA File No.: 165628 CE marking UL File No.: E36332
Product Tradename	U-PKZ0
Product Type	Accessory
Product Sub Type	Undervoltage Release
Electric connection type	Screw connection
Suitable for	Motor safety switch
Voltage type	AC
Rated control supply voltage (Us) at AC, 50 Hz - min	230 V
Rated control supply voltage (Us) at AC, 50 Hz - max	230 V
Rated control supply voltage (Us) at AC, 60 Hz - min	0 V
Rated control supply voltage (Us) at AC, 60 Hz - max	0 V
Rated control supply voltage (Us) at DC - min	0 V
Rated control supply voltage (Us) at DC - max	0 V
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	0
Number of contacts (normally open contacts)	0

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Under voltage coil (EC001022)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Undervoltage trip (ecl@ss10.0.1-27-37-04-17 [AKF015013])		
Rated control supply voltage Us at AC 50HZ	V	230 - 230
Rated control supply voltage Us at AC 60HZ	V	0 - 0
Rated control supply voltage Us at DC	V	0 - 0
Voltage type for actuating		AC
Type of electric connection		Screw connection
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Delayed		No
Suitable for power circuit breaker		No
Suitable for off-load switch		No

Suitable for motor safety switch		Yes
Suitable for overload relay		No