



Main terminal max.16mm<sup>2</sup>

Part no. **AK16**  
 Catalog No. **079336**

### Delivery program

Product range		General switchboard accessories
Accessories		Ultra-flat busbar terminals
Accessories		Termination expansion for ultra-flat busbar terminals
Description		Expansion terminals for strap
For use with busbars	mm	Cu 10 x 3
Connection cross-sections round conductor type:	mm <sup>2</sup>	<input type="radio"/> 1.5 - 16 <input checked="" type="radio"/> 0.75 - 16
<input type="radio"/> solid <input checked="" type="radio"/> stranded <input checked="" type="radio"/> flexible with ferrule		
Note for table header		
Terminal capacities:		
<input type="radio"/> Solid <input checked="" type="radio"/> Stranded <input checked="" type="radio"/> Flexible with ferrule		

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)		
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])		
Busbar thickness	mm	3 - 3
Busbar width	mm	10 - 10
Suitable for		Other
Width clamp	mm	10
Max. conductor cross section	mm <sup>2</sup>	16
Max. rated operation current Ie	A	63
Suitable for round conductor connection		Yes
Suitable for sector conductor connection		No
Suitable for strip conductor connection		No