



Busbar terminal, 1600A, for copper band

Part no. K30X10L
Catalog No. 081977

Delivery program

Product range			Ci insulated enclosures
Basic function			Prepared enclosures
Product function			Accessories for busbar enclosures
Accessories			Busbar terminals
Function			Connection for flat cable and cu bar
For use with busbars		mm	Cu 2 x 30 x 10
Terminal capacity for flat strip		mm	2 x 50 x 12
Notes For main conductor L1, L2, L3			

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])			
Busbar thickness		mm	10 - 10
Busbar width		mm	30 - 60
Suitable for			Flat rail
Width clamp		mm	17
Max. conductor cross section		mm ²	1000
Max. rated operation current Ie		A	1600
Suitable for round conductor connection			No
Suitable for sector conductor connection			No
Suitable for strip conductor connection			Yes

Additional product information (links)

allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&model certification xEnergy Safety Ci
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&Save time – we assist you with expert pre-assembly
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&product information xEnergy Safety Ci
tool for calculating the power loss for switching device combinations	http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm

