



Side walls (1 pair), closed, for HxD = 2000 x 300mm, IP55, grey

Part no. XLSS203
Catalog No. 114720
EL-Nummer (Norway) 2460115

Delivery program

| | | |
|--------------------------------------|--|--|
| Product range | | Control centres XVTL |
| Basic function | | Combination enclosures |
| Product function | | Accessories |
| Accessories | | Enclosure side plates |
| Single unit/Complete unit | | Modular system |
| Function | | Enclosure side plates for protection type IP55 to IEC/EN 60529 and IEC/EN 529 For terminating a panel row |
| Information about equipment supplied | | Enclosure side plates, in pairs Countersunk screws included as standard |
| Description | | External fixing with self-threading, self-grounding countersunk screws |
| Material | | Sheet steel 1.25 mm |
| Surface finish | | Polyester powder coating RAL 7035, light grey |
| Suitable for depth | | 300 |
| Suitable for height | | 2000 |
| Protection type | | IP55 |

Technical data ETIM 7.0

| | | | |
|--|--|----|----------------|
| Cabinet enclosures (EG000011) / Side/back panel (switchgear cabinet) (EC002524) | | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Panel (electrical cabinet) / Side/back panel (electrical cabinet) (ecl@ss10.0.1-27-18-21-01 [AKE423014]) | | | |
| Suitable as side panel | | | Yes |
| Suitable as rear panel | | | No |
| Modular spacing | | mm | 25 |
| Suitable for enclosure building width | | mm | 0 |
| Suitable for enclosure building depth | | mm | 300 |
| Width | | mm | 190 |
| Height | | mm | 1907 |
| Material | | | Steel |
| Surface finishing | | | Powder coating |
| Colour | | | Grey |
| RAL-number | | | 7035 |

| | | | |
|------------------------|--|--|----|
| With cable entry | | | No |
| Number of height units | | | 0 |
| With lock | | | No |