Secondary terminal wire kit, through connection for DMVS160N/DMV 250N $\,$



Part no. SETDMVS160N/250N 1314878

Product name	
1 TOURIST TRAINS	Eaton DMV Accessory Bridge connector set
Part no.	SETDMVS160N/250N
EAN	8711426101258
Product Length/Depth	232 millimetre
Product height	122 millimetre
Product width	116 millimetre
Product weight	1.2 kilogram
Compliances	CE
Product Tradename	DMV
Product Type	Accessory
Product Sub Type	Bridge connector set
Accessory/spare part type	Connecting bridge
Туре	Connection kit for changeover mechanism Connection set
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	50 °C
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	250 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.8 Connections for external conductors 10.9.2 Power-frequency electric strength	is the patier builder's responsibility.
	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	
10.9.2 Power-frequency electric strength 10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength 10.9.3 Impulse withstand voltage 10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility. Is the panel builder's responsibility. The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.9.2 Power-frequency electric strength 10.9.3 Impulse withstand voltage 10.9.4 Testing of enclosures made of insulating material 10.10 Temperature rise	Is the panel builder's responsibility. Is the panel builder's responsibility. The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. Is the panel builder's responsibility. The specifications for the switchgear must I

Technical data ETIM 8.0 Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498) Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013]) Type of accessory/spare part Accessory Connecting bridge Yes

No

Spare part