



Connection cable, 4p, DC current, coupling M12 flat, plug, angled, L=3m



Part no. CSDR4A4CY2203-D
Catalog No. 136315
Alternate Catalog No. CSDR4A4CY2203-D
EL-Nummer (Norway) 0004315405

Delivery program

Basic function			Accessories
Accessories			Connecting cables
Length		mm	3000
Pin assignment			
Voltage type			DC
Number of poles			4 pole
Style output side			Plug, angled
Style input side			Coupling, straight
For use with			
For use with			DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])			
Number of poles			4
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Straight
Type of electrical connection, box-sided			M12
Type of plug-in contact, box-sided			Male (plug)
Positioning cable feed, box-sided			Angled
Cable length		m	3
Material of cable sheath			Other
Halogen free			No
Colour cable sheath			Other
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			Other
Material of contact surface			Other
Permitted cable outer temperature after assembling without vibration		°C	40 - 70
Permitted cable outer temperature during assembling/handling		°C	40 - 70
Rated current In		A	0
Rated voltage		V	0
Continuity resistor		mOhm	0
Degree of protection (IP)			Other

Approvals

Product Standards

CE marking