

Lightning current and surge arresters kit, TN-C kit, 3p



Part no. SPBT12-280/3
158330
EL Number 1609777
(Norway)

Product name	Eaton Moeller series xPole - SPBT12 Surge Protection Device
Part no.	SPBT12-280/3
EAN	4015081548880
Product Length/Depth	86 millimetre
Product height	69 millimetre
Product width	52.5 millimetre
Product weight	0.429 kilogram
Compliances	RoHS conform
Product Tradename	xPole - SPBT12
Product Type	Surge Protection Device
Product Sub Type	None
Application	Open areas Residential buildings Utility buildings
Number of poles	Three-pole
Type	Surge arrester
Voltage protection level	1.5 kV
Voltage protection level (DC+ - DC-)	0 kV
Voltage protection level (DC+/DC- - PE)	0 kV
Voltage protection level (L-N)	0 kV
Voltage protection level (L-PE)	1.5 kV
Voltage protection level (N-PE)	0 kV
Nominal voltage at AC	280 V
Nominal voltage at DC	0 V
Continuous voltage at AC - max	280 V
Continuous voltage at DC - max	0 V
PV-voltage - max	0 V
Lightning impulse current (10/350 µs)	12.5 kA
Follow current extinguishing capability	0 kA
Signalling at the device	Optic
Specific energy (W/R)	39.1 kJ/Ohm
Frame	3 modular spacing
Mounting method	DIN rail (top hat rail) 35 mm
Conductor cross section (flexible, fine-strand) - min	mm ²
Conductor cross section (flexible, fine-strand) - max	35 mm ²
Conductor cross section (solid, solid-strand) - min	mm ²
Conductor cross section (solid, solid-strand) - max	25 mm ²
Degree of protection	IP20
System configuration type	Other TN-C-S TN-C TN TN-S TT
Test class	Type 1 + 2

Technical data ETIM 8.0

Earthing, lightning and surge protection (EG000021) / Combined arrester for power supply systems (EC001457)		
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Combined lightning current/surge arrester f. power supply s. (ecl@ss10.0.1-27-13-08-08 [ACN284011])		
System configuration DC		No
System configuration IT		No
System configuration TN		Yes
System configuration TN-C		Yes
System configuration TN-C-S		Yes
System configuration TN-S		Yes
System configuration TT		No
System configuration other		Yes
Number of poles		3
Lightning impulse current (10/350 µs)	kA	12.5
Max. continuous voltage AC	V	280
Max. continuous voltage DC	V	0
Nominal voltage AC	V	280
Nominal voltage DC	V	0
Max. PV-voltage	V	0
Voltage protection level	kV	1.5
Voltage protection level L-N	kV	0
Voltage protection level L-PE	kV	1.5
Voltage protection level N-PE	kV	0
Voltage protection level (DC+ - DC-)	kV	0
Voltage protection level (DC+/DC- - PE)	kV	0
Follow current extinguishing capability	kA	0
Specific energy (W/R)	kJ/Ohm	39.1
Max. overcurrent protection device, parallel connection (fuse)	A	0
Max. overcurrent protection device, series connection (fuse)	A	160
Mounting method		DIN rail (top hat rail) 35 mm
Construction size		3 modular spacing
Max. conductor cross section solid (solid, stranded)	mm ²	25
Max. conductor cross section flexible (fine-strand)	mm ²	35
Remote signalling		No
Signalling at the device		Optic
Test class		Type 1 + 2
Integrated backup fuse		No
Energy-coordinated protection effect with regard to the terminal equipment		No
Voltage switching spark gap technology		No
Overcurrent protected voltage tapping		No
Degree of protection (IP)		IP20