

Compact PLC, 24 V DC, ethernet, RS232, RS485, CAN



**Part no.**                    **XC-152-D6-11**  
**167855**  
**EL Number**                **4560850**  
**(Norway)**

Product name	Eaton XC Compact PLC
Part no.	XC-152-D6-11
EAN	4015081644308
Product Length/Depth	50.6 millimetre
Product height	102.6 millimetre
Product width	155 millimetre
Product weight	0.29 kilogram
Certifications	UL Category Control No.: NRAQ CSA Class No.: none CULus CE UL 508 EN 61131 UL File No.: E205091 DNV GL UL IEC/EN 61131-2, CE UL508 CSA File No.: UL report applies to both US and Canada Certified by UL for use in Canada
Product Tradename	XC
Product Type	Compact PLC
Product Sub Type	None
Catalog Notes	CoDeSys Runtime (license inclusive)
Features	Integrated Web server
Fitted with:	Libraries Engineering software Visualization Documentation Programming interface Real time clock Basic device Power supply Communication module Technology module Memory unit Function module Other components
Functions	Building blocks Web-server Additional field bus interfaces OPC Server Remote Server
Processor	RISC CPU, 32 Bit, 400 MHz
Battery runtime	10 years typ.
Degree of protection	IP20
Memory capacity	64 MegaByte/4 kByte/32 kByte (Application/marker/retain data)
Operating system	Windows CE 5.0 (license included)
Power loss	Max. 8.5 W
Rated operational voltage	20.4 - 28.8 V DC
Supply voltage at DC - max	24
Ambient operating temperature - min	0 °C
Ambient operating temperature - max	55 °C
Ambient storage temperature - min	-20 °C
Ambient storage temperature - max	60 °C

Connection to SmartWire-DT		No
Connection type		Ethernet: RJ45 plug, 8-pole CAN: 9-pole SUB-D (plug) RS232: SUB-D, 9-pole (plug)
Cycle time		< 0.04 ms, for 1 k of instructions (Bit, Byte), memory
Data transfer rate		1000 kBit/s, CAN 57.6 kBit/s, RS232 57.6 kBit/s, RS485 100Base-TX, Ethernet 10Base-T, Ethernet
Interfaces		RS232 1 x USB host 2.0 (built-in) USB 2.0 1 x RS485 (built-in) 1 x CANopen®/easyNet (built-in) CAN 1 x RS232 (built-in) 1 x Ethernet 10/100 Mbps (built-in) 1 x USB device 2.0 (built-in) USB 2.0 (Host)
Memory		64 MByte Program memory code
Number of modules		127 (CAN)
Number of slots		1 (for SD-Card)
Protocol		UDP (basic interface) TCP (basic interface) FTP (basic interface) HTTP (basic interface) IP (basic interface) CANopen® (additional interface) SMTP (basic interface) easyNet - Master/Device (additional interface)
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		6 W
Heat dissipation details		6 W for basic device + 2.5 W for USB module With power consumption for 24 V
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / PLC device set (EC002581)

Electric engineering, automation, process control engineering / Control / Programmable logic control (SPS) / PLC device set (ecl@ss10.0.1-27-24-22-19 [BAA707013])

Contains function building blocks			Yes
Contains basic device			Yes
Contains module rack			No
Contains power supply			Yes
Contains analogue input module			No
Contains analogue output module			No
Contains digital input module			No
Contains digital output module			No
Contains function module			Yes
Contains technology module			Yes
Contains communication module			Yes
Contains memory unit			Yes
Contains simulation module			No
Contains connection cable			No
Contains control unit			No
Contains monitor			No
Contains programming software			No
Contains engineering software			Yes
Contains visualization			Yes
Contains libraries			Yes
Contains documentation			Yes
Contains other components			Yes
Software preinstalled			No