



Filament lamp, 230V, 4W

Part no. **SL4-L230**
 Catalog No. **171385**
 Alternate Catalog No. **SL4-L230**
 EL-Nummer (Norway) **4137620**

Delivery program

| | | | |
|----------------------------|----------------|---|----------------|
| Product range | | | Accessories |
| Basic function accessories | | | Filament bulbs |
| Mounting | | | Ba15d |
| lifespan | | h | 3000 |
| Power | | | 4 W |
| Rated operational voltage | U _e | V | 230 V |
| For use with | | | SL4-L-... |
| Connection to SmartWire-DT | | | no |

Design verification as per IEC/EN 61439

| | | | |
|--|--|----|-----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | | °C | -30 |
| Operating ambient temperature max. | | °C | 60 |

Technical data ETIM 7.0

| | | | |
|---|--|----|-------------------|
| Lamps (EG000028) / Indication- and signalling lamp (EC000399) | | | |
| Electric engineering, automation, process control engineering / Lighting installation, device / Light medium / Indication- and signal lamp (ecl@ss10.0.1-27-11-06-31 [AKE242014]) | | | |
| Lamp power | | W | 4 - 4 |
| Lamp voltage | | V | 230 - 230 |
| Luminous flux | | lm | 0 |
| Socket | | | BA15d |
| Technology | | | Incandescent lamp |
| Lamp shape | | | Other |
| Halogen | | | No |
| Krypton | | | No |
| Xenon | | | No |
| Colour | | | None |
| Colour temperature | | K | 2800 |
| Diameter | | mm | 0 |
| Total length | | mm | 0 |
| Suitable for torches | | | No |
| Suitable for pointer | | | Yes |
| Suitable for round flashing luminaire | | | Yes |
| Nominal current | | mA | 0 |
| Average nominal lifespan | | h | 3000 |
| Energy efficiency class | | | |

Dimensions

