

Continuous light module; yellow; LED;230 V



Part no. SL7-L230-Y
171477
EL Number 4137731
(Norway)

Product name	Eaton Moeller® series SL7 Continuous light module
Part no.	SL7-L230-Y
EAN	4015081678020
Product Length/Depth	73 millimetre
Product height	73 millimetre
Product width	73 millimetre
Product weight	0.082 kilogram
Certifications	CE IEC/EN 60947-5-1 Certified by UL for use in Canada UL 508 UL UL Category Control No.: NKCR IEC/EN 60529 UL report applies to both US and Canada UL File No.: E29184 CSA-C22.2 No. 14-10 CSA-C22.2 No. 94-91 CSA Class No.: NKCR7
Product Tradename	SL7
Product Type	Continuous light module
Product Sub Type	None
Color	Yellow
Enclosure color	Black
Functions	Continuous light
Light modules	LED
Number of modules	Max. 5 (with standard base) Max. 10 (with base for mounting on both sides)
Connection to SmartWire-DT	No
Current consumption	0.027 - 0.028 A, at 230/240 V AC
Degree of protection	NEMA 13 IP66
Lifespan, electrical	100,000 h
Light type	Continuous light
Material	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Radiation angle	360 °
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Type	Continuous light module
Voltage type	AC
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	60 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Leakage current		0.003 A
Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) at AC - min		230 V
Rated operational voltage (Ue) at AC - max		240 V
Rated operational voltage (Ue) at DC - min		0 V
Rated operational voltage (Ue) at DC - max		0 V

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss10.0.1-27-37-12-20 [AKF038014])		
Function		Continuous light
Colour		Yellow
Outer diameter	mm	73
Operating voltage at AC 50 Hz	V	230 - 240
Operating voltage at AC 60 Hz	V	230 - 240
Operating voltage at DC	V	0 - 0
Voltage type		AC
Lamp type		LED
Colour housing		Black
Degree of protection (IP)		IP66
Degree of protection (NEMA)		13