

Insulated enclosure, HxWxD=280x200x160mm, +mounting plate



Part no. CI-K5-160-M
206900
EL Number 4138013
(Norway)

Product name	Eaton Moeller® series CI-K Insulated enclosure
Part no.	CI-K5-160-M
EAN	4015082069001
Product Length/Depth	280 millimetre
Product height	125 millimetre
Product width	200 millimetre
Product weight	1.47 kilogram
Certifications	IEC/EN 60529 UL94: HB IEC 60068-2-11 DIN EN 62208 UL94: V0/1.5 mm thickness
Product Tradename	CI-K
Product Type	Insulated enclosure
Product Sub Type	None
Catalog Notes	Lamp indicator L-... can be mounted in base knock-out M20/M25
Enclosure color	Light gray, Cover (RAL 7035) Black (RAL 9005) Light gray, Operator (RAL 7035)
Enclosure material	1 Ω x 10 ¹³ (Surface resistance to IEC 60093) Plastic
Features	UV resistance beneath protective shield Halogen free
Fitted with:	Control cable entry DIN-rail Weight of fitted components: max. 1.7 kg
Knockouts	Hard knockout version Metric cable entry knockouts at the top, bottom and back plate
Cover material	Glass-fiber reinforced polycarbonate
Degree of protection	IP65 NEMA Other
Degree of protection (front side)	IP65
Dielectric strength	30 kV/mm, according to IEC 60243-1
Flammability characteristics	960 °C/1 mm thickness (base, cover; glow wire to VDE 0471 Part 2) 650 °C/1 mm thick (push-through membrane) to VDE 0471 Part 2)
Model	Surface mounting
Mounting depth	133 mm
Mounting weight capacity - max	1 kg
Product category	Empty enclosures
Suitable for	Emergency stop
Surface treatment	Resistant to corrosion
Track resistance	CTI 175 (cover, to IEC 60112) CTI 175 (base, to IEC 60112)
Type	Basic enclosure
Water consumption	0.29 % (According to DIN EN ISO 62)
Environmental resistance	Partly resistant to greases Chemical resistant (Base, Cover) Not resistant to alkalis Chemical resistant (Push-through membrane (CI-K1/CI-K2) and sealing material) Partly resistant to acids (> 10%) Partly resistant to benzene Resistant against acids (< 10%) Not resistant to Mineral oil

		Resistant against benzene Partly resistant to alcohol Not resistant to benzene Resistant against alcohol Resistant against alkalis Resistant against gasoline Resistant against salt solutions Resistant against greases Resistant against mineral oil
Impact resistance		IK06 (according to EN 50102)
Temperature resistance		-40 - 80 °C (gasket) -40 - 120 °C (enclosure)
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Equipment heat dissipation, current-dependent P _{vid}		0 W
Heat dissipation capacity P _{diss}		41 W
Heat dissipation per pole, current-dependent P _{vid}		0 W
Rated operational current for specified heat dissipation (I _n)		0 A
Static heat dissipation, non-current-dependent P _{vs}		0 W
Radiated heat dissipation with separate mounting		41 W (at an ambient temperature of 20 °C)
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Not applicable.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Meets the product standard's requirements.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecI@ss10.0.1-27-37-13-01 [AKN343014])			
Material housing			Plastic
Width		mm	200
Height		mm	125
Depth		mm	280
With transparent cover			No
Suitable for emergency stop			Yes
Model			Surface mounting
Degree of protection (IP)			IP65

