

## Surface mounting enclosure, 6 mounting locations

**Part no.** M22-I6  
**216540**

**EL Number**  
**(Norway)** 4355388

Product name	Eaton Moeller® series M22 Accessory Surface mounting enclosure
Part no.	M22-I6
EAN	4015082165406
Product Length/Depth	80 millimetre
Product height	56 millimetre
Product width	252 millimetre
Product weight	0.362 kilogram
Compliances	CE Marked
Certifications	IEC 60947-5 CSA Std. C22.2 No. 14-05 EN 60947-5 CSA Std. C22.2 No. 94-91 VDE UL 508 CE UL UL File No.: E29184 CSA File No.: 012528 CSA Class No.: 3211-03 CSA-C22.2 No. 14-05 UL Category Control No.: NKCR IEC/EN 60947-5 CSA-C22.2 No. 94-91 CSA
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Surface mounting enclosure
Color	Gray
Enclosure color	Gray
Enclosure material	Plastic
Fitted with:	High-grade steel screws
Knockouts	2 x M20/25 (cable entry knockout at the side, 1 x each side) 2 x M20 (cable entry knockouts at the top) 2 x M20 (cable entry knockouts at the rear)
Number of locations	6
RAL-number	7035
Accessories	High-grade steel screws
Degree of protection	IP66 NEMA 3R
Opening diameter	22.5 mm
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Connection to SmartWire-DT	No
Force for positive opening - min	0 N
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss10.0.1-27-37-12-05 [AKF023014])			
Number of command positions			6
Construction type housing			Surface mounting housing
Material housing			Plastic
Housing material quality			Other
Diameter openings		mm	22.5
Colour housing cover			Grey
Degree of protection (IP)			IP66
Degree of protection (NEMA)			3R
Width		mm	252
Height		mm	56
Depth		mm	80