## DATASHEET - FAZ6-B6/3



Miniature circuit breaker (MCB), 6 A, 3p, characteristic: B, 6 kA

Part no.FAZ6-B6/3Catalog No.239110Alternate CatalogFAZ6-B6/3



## Design verification as per IEC/EN 61439

No.

I <sub>n</sub>	A	6
	А	6
		0
P <sub>vid</sub>	W	5.5
		Meets the product standard's requirements.
		Meets the product standard's requirements.
		Meets the product standard's requirements.
t		Meets the product standard's requirements.
		Meets the product standard's requirements.
		Does not apply, since the entire switchgear needs to be evaluated.
		Does not apply, since the entire switchgear needs to be evaluated.
		Meets the product standard's requirements.
		Does not apply, since the entire switchgear needs to be evaluated.
		Meets the product standard's requirements.
		Does not apply, since the entire switchgear needs to be evaluated.
		Does not apply, since the entire switchgear needs to be evaluated.
		Is the panel builder's responsibility.
		Is the panel builder's responsibility.
		Is the panel builder's responsibility.
		Is the panel builder's responsibility.
		Is the panel builder's responsibility.
		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## **Technical data ETIM 7.0**

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)

Electric engineering, automation, process control engineering / Electrical installation, betwee / Ministure circuit breaker (MCB)     Release characteristic   a   B     Number of poles (total)   a   a   a     Number of potected poles   a   a   a   a   a     Red current   A   b   a			
Number of poles (total)   Image: Pole of total     Number of protected poles   Image: Pole of total     Rated current   Image: Pole of total     Rated voltage   Image: Pole of total     Rated insulation voltage Uinp   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     Rated short-circuit breaking capacity Icn EN 60898 at 400 V   Image: Pole of total     <		/ Miniature ci	rcuit breaker system (MCB) / Miniature circuit breaker (MCB)
Number of protected polesSRated currentA6Rated voltageV30Rated insulation voltage UiV40Rated insulation voltage UinpKV40Rated short-circuit breaking capacity Icn EN 60898 at 230 VKA6Rated short-circuit breaking capacity Icn EN 60898 at 400 VKA6Rated short-circuit breaking capacity Icn EN 60898 at 400 VKA6Rated short-circuit breaking capacity Icn EN 60898 at 400 VKA6Rated short-circuit breaking capacity Icn EN 60897-2 at 230 VKA6	Release characteristic		В
Rated currentA6Rated voltageV30Rated insulation voltage UinpV440Rated insulation voltage UinpKV4Rated short-circuit breaking capacity Icn EN 60898 at 400 VKA6Rated short-circuit breaking capacity Icn EN 60898 at 400 VKA6Rated short-circuit breaking capacity Icn EN 60898 at 400 VKA6Rated short-circuit breaking capacity Icn EN 60898 at 400 VKA6Rated short-circuit breaking capacity Icn EN 60898 at 400 VKA6Rated short-circuit breaking capacity Icn EN 60897-2 at 230 VKA6	Number of poles (total)		3
Rated voltageV20Rated insulation voltage UiV40Rated impulse withstand voltage UimpKV4Rated short-circuit breaking capacity Icn EN 60898 at 230 VKA6Rated short-circuit breaking capacity Icn EN 60898 at 400 VKA6Rated short-circuit breaking capacity Icn EN 60898 at 400 VKA6Rated short-circuit breaking capacity Icn EN 60897-2 at 230 VKA6	Number of protected poles		3
Rated insulation voltage Uinp V 440   Rated impulse withstand voltage Uimp KV 4   Rated short-circuit breaking capacity Icn EN 60898 at 230 V KA 6   Rated short-circuit breaking capacity Icn EN 60898 at 400 V KA 6   Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V KA 10	Rated current	А	6
Rated impulse withstand voltage Uimp kV 4   Rated short-circuit breaking capacity Icn EN 60898 at 230 V kA 6   Rated short-circuit breaking capacity Icn EN 60898 at 400 V kA 6   Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V kA 10	Rated voltage	V	230
Rated short-circuit breaking capacity Icn EN 60898 at 230 V kA 6   Rated short-circuit breaking capacity Icn EN 60898 at 400 V kA 6   Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V kA 6	Rated insulation voltage Ui	V	440
Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V kA 6	Rated impulse withstand voltage Uimp	kV	4
Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V kA 10	Rated short-circuit breaking capacity Icn EN 60898 at 230 V	kA	6
	Rated short-circuit breaking capacity Icn EN 60898 at 400 V	kA	6
Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V kA 10	Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V	kA	10
	Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V	kA	10

Voltage type		AC
Frequency	Hz	50 - 60
Current limiting class		3
Suitable for flush-mounted installation		No
Concurrently switching N-neutral		No
Over voltage category		3
Pollution degree		2
Additional equipment possible		Yes
Width in number of modular spacings		3
Built-in depth	mm	70.5
Degree of protection (IP)		IP20
Ambient temperature during operating	°C	-25 - 75
Connectable conductor cross section multi-wired	mm²	1 - 25
Connectable conductor cross section solid-core	mm²	1 - 25

## Additional product information (links)

Temperature dependency, derating

https://www.eaton.com/content/dam/eaton/technicaldocumentation/technical-data-tables/Derating table FAZ6.pdf