




**Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS, 2W, 0.5HP**

**Part no. ZP-NHK**  
**Catalog No. 248437**

**EL-Nummer (Norway) 1609489**

**Delivery program**

|                            |  |  |   |
|----------------------------|--|--|---|
| Basic function             |  |  | Accessories for combined residual-current/power circuit-breakers<br>Accessories for miniature circuit-breaker |
| Basic function accessories |  |  | Tripping signal contacts  |
| Application                |  |  | Switchgear for industrial and advanced commercial applications  |
| Product range              |  |  | Accessory   |
| Side mounting              |  |  | for fitting on left to: LS, FI/LS   |
| Contact sequence           |  |  |                             |

**Technical data**

**Design verification as per IEC/EN 61439**

|  |  |    |    |
|--|--|----|----|
| Technical data for design verification |  |    |    |
| Operating ambient temperature min.     |  | °C | -5 |
| Operating ambient temperature max.     |  | °C | 40 |

**Technical data ETIM 7.0**

|  |  |   |                   |
|--|--|---|-------------------|
| Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)   |  |   |                   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ec@ss10.0.1-27-14-35-02 [AKE327013]) |  |   |                   |
| Device fitting   |  |   | Universal         |
| Additional equipment   |  |   | Signalling switch |
| Attached at delivery   |  |   | No                |
| Assembly width (TE)  |  |   | 0.5               |
| Number of contacts as normally open contact  |  |   | 0                 |
| Number of contacts as normally closed contact  |  |   | 0                 |
| Number of contacts as change-over contact  |  |   | 2                 |
| Number of fault-signal switches  |  |   | 0                 |
| Rated switch current   |  | A | 4                 |
| Rated voltage  |  | V | 250               |
| Voltage type for actuating   |  |   | AC                |
| With auto test for earth leakage function  |  |   | No                |
| Suitable for max. number of poles main contact unit (total)  |  |   | 2                 |
| Suitable for max. current main contact unit  |  | A | 4                 |

## Dimensions

