

## Auxiliary contact, 1N/0+1N/C

**Part no.**                    **Z-SC**  
                                       **248862**  
**EL Number**                **4355534**  
**(Norway)**

Product name		Eaton Distribution parts
Part no.		Z-SC
EAN		4015082488628
Product Length/Depth		87.5 millimetre
Product height		60 millimetre
Product width		8.75 millimetre
Product weight		0.026 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
PDH Status		Active
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Additional equipment required		Auxiliary switch
Ambient operating temperature - max		60 °C
Ambient operating temperature - min		-40 °C
Assembly width		0.5
Device fitting		Auxiliary switch / relay
EL number		4355534
Equipment heat dissipation, current-dependent		0 W
Heat dissipation per pole, current-dependent		0.5 W
Main contact unit current rating - max		63 A
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles at main contact unit - max		4
Number of switches (fault signal)		0
Rated operational current for specified heat dissipation (I <sub>n</sub> )		3 A
Rated operational voltage (U <sub>e</sub> ) - max		230 V
Rated switch current		3 A
Rated switch current [7EF006706]		A
Rated voltage [7EF000228]		V
Static heat dissipation, non-current-dependent		0 W
Suitable for max. current main contact unit [7EF008730]		A
Voltage type		AC

## Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])		
Device fitting		Auxiliary switch / relay
Additional equipment		Auxiliary switch
Installed at the factory		No
Width in number of modular spacings		0.5

Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	3
Rated voltage	V	230
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		4
Suitable for max. current main contact unit	A	63