



Filament lamp, 110-130V, BA 9s, 2.4W

Part no. A22-GL130
Catalog No. 261361
Alternate Catalog No. A22-GL130

Delivery program

			This item is no longer available. No direct reference, please use RMQ M22-....
Accessories			General accessories
Basic function accessories			Filament bulbs high-grade versions from selected manufacturers
Type			110 - 130 V/2.4 W
Lifespan to EN 60064 at $t_a = +25\text{ }^\circ\text{C}$	t_{mean} (AC)	h	2000
Connection to SmartWire-DT			no

Technical data

General

Ambient temperature			
Open		$^\circ\text{C}$	-25 - +70

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		$^\circ\text{C}$	-25
Operating ambient temperature max.		$^\circ\text{C}$	70

Technical data ETIM 7.0

Lamps (EG000028) / Indication- and signalling lamp (EC000399)			
Electric engineering, automation, process control engineering / Lighting installation, device / Light medium / Indication- and signal lamp (ecl@ss10.0.1-27-11-06-31 [AKE242014])			
Lamp power		W	
Lamp voltage		V	130 - 130
Luminous flux		lm	0
Socket			BA9s
Technology			LED
Lamp shape			Pear-shape
Halogen			No
Krypton			No
Xenon			No
Colour			None
Colour temperature		K	0
Diameter		mm	0
Total length		mm	0
Suitable for torches			No
Suitable for pointer			Yes
Suitable for round flashing luminaire			
Nominal current		mA	22
Average nominal lifespan		h	2000
Energy efficiency class			

Additional product information (links)

IL04716002Z (AWA1160-1745) RMQ-Titan System	
IL04716002Z (AWA1160-1745) RMQ-Titan System	https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716002Z2020_09.pdf

