

Programming cable, serial, XC100/200, EC4P, RJ45, sub-D 9pole, 2m



Part no. XT-SUB-D/RJ45
262186
EL Number 4519655
(Norway)

Product name	Eaton XT Accessory Programming cable
Part no.	XT-SUB-D/RJ45
EAN	4015082621865
Product Length/Depth	200 millimetre
Product height	20 millimetre
Product width	140 millimetre
Product weight	0.13 kilogram
Compliances	CE
Product Tradename	XT
Product Type	Accessory
Product Sub Type	Programming cable
Functions	PLC - PC
Number of Poles	Eight-pole
Cable length	3 m
Suitable for	Digital signals Input board PLC Analogue signals Output card PLC
Ambient operating temperature - min	0 °C
Ambient operating temperature - max	55 °C
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdis	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Meets the product standard's requirements.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility.

10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / PLC connection cable (EC000237)		
Electric engineering, automation, process control engineering / Control / Programmable logic control (SPS) / SPS cable connection (ecl@ss10.0.1-27-24-22-20 [AFR598003])		
Function		PLC - PC
Length	m	3
Suitable for input board PLC		Yes
Suitable for output card PLC		Yes
Suitable for digital signals		Yes
Suitable for analogue signals		Yes
Type of electrical connection, field-sided		Connection plug board
Type of electrical connection, box-sided		RJ-plug
Number of poles		8