



Entry, flat cable, for enclosures

Part no. RA-C1-DF
Catalog No. 264243
Alternate Catalog No. RA-C1-DF

Delivery program

Product range		Power supply at flat cable RA-C1
Subrange		Flexible busbar bushing
Basic function		for bushing for flat cable in distributor module or control cabinet
For use with		
For use with		RA-C1-VM-7

Technical data ETIM 7.0

Cable and wire entry systems (EG000009) / Cable entry sleeve (EC000879)		
Electric engineering, automation, process control engineering / Electrical installation, device / Connection devices / Feed through spout (ecl@ss10.0.1-27-14-44-21 [AD1139007])		
Model		Other
Insert for cable gland		No
Cable entry		Long-slot
Number of cables		1 - 1
Suitable for cable diameter	mm	0 - 0
Bore diameter	mm	0
For wall thickness	mm	0 - 0
Thread size (metric)		0
Thread size PG		0
Total length	mm	0
With strain relief		No
Shrink technique		No
Angle model		No
Material		Plastic
Material quality		Polyvinyl chloride (PVC)
Surface protection		Untreated
Halogen free		Yes
Colour		Black
Gastight		No
Fire resistant		No
Watertight		Yes
Degree of protection (IP)		IP65
Working temperature	°C	-10 - 55

Assets (links)

Instruction Leaflets

IL03406020Z2018_05

Manuals

MN03406003Z_EN (English)

Additional product information (links)

IL03406020Z Rapid Link: Speed Control Unit	
IL03406020Z Rapid Link: Speed Control Unit	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03406020Z2018_05.pdf
MN03406003Z Rapid Link 4.0	
MN03406003Z Rapid Link 4.0 - Deutsch	ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN03406003Z_DE.pdf
MN03406003Z Rapid Link 4.0 - English	ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN03406003Z_EN.pdf
MN03406003Z Rapid Link 4.0 - français	ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN03406003Z_FR.pdf

