

Auxiliary contact, for PFDM, 1W+1N/C, 0.5HP

Part no. **Z-HD**
265620

Product name		Eaton Distribution parts
Part no.		Z-HD
EAN		4015082656201
Product Length/Depth		88 millimetre
Product height		75 millimetre
Product width		22 millimetre
Product weight		0.043 kilogram
Compliances		RoHS conform
Certifications		EN45545-2 IEC 61373
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
PDH Status		Active
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Accessory/spare part type		Auxiliary contacts
Additional equipment required		Auxiliary switch
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Application		Switchgear for industrial and advanced commercial applications
Assembly width		0.5
Device fitting		Earth leakage switch
Mounting method		For fitting on left to: FI
Number of contacts (change-over contacts)		1
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		0
Number of poles at main contact unit - max		2
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		230 V
Rated switch current		3 A
Rated switch current [7EF006706]		A
Rated voltage [7EF000228]		V
Suitable for current of main contact unit - max		6 A
Suitable for max. current main contact unit [7EF008730]		A
Type		Accessory Accessory for residual current circuit breaker
Used with		Auxiliary contacts Accessory Accessory for residual current circuit breaker
Voltage type		AC

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])		
Device fitting		Earth leakage switch
Additional equipment		Auxiliary switch

Installed at the factory		No
Width in number of modular spacings		0.5
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		1
Number of fault-signal switches		0
Rated switch current	A	3
Rated voltage	V	230
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		2
Suitable for max. current main contact unit	A	6