



Label, emergency switching off, yellow, blank




**Part no.** M22-XBK  
**Catalog No.** 269580  
**Alternate Catalog No.** M22-XBKQ  
**EL-Nummer (Norway)** 4315306

### Delivery program

|                            |  |                       |
|----------------------------|--|-----------------------|
| Product range              |  | Accessories           |
| Basic function accessories |  | Emergency-stop labels |
| Form                       |  | Diameter = 60 mm      |
| Name                       |  | Blank                 |
| <b>Colour</b>              |  | yellow                |
|                            |  |                       |
| RAL Value                  |  | RAL 1004              |
| Degree of Protection       |  | IP66                  |
| Connection to SmartWire-DT |  | no                    |

### Technical data

#### General

|                         |    |  |
|-------------------------|----|--|
| Degree of Protection    |    | IP66   |
| Ambient temperature     |    |  |
| Open                    | °C | -25 - +70  |
| shipping classification |    | DNV<br>GL<br>LR  |
|                         |    |    |

### Design verification as per IEC/EN 61439

|  |            |    |  |
|--|------------|----|--|
| Technical data for design verification                   |            |    |  |
| Rated operational current for specified heat dissipation | $I_n$      | A  | 0  |
| Heat dissipation per pole, current-dependent             | $P_{vid}$  | W  | 0  |
| Equipment heat dissipation, current-dependent            | $P_{vid}$  | W  | 0  |
| Static heat dissipation, non-current-dependent           | $P_{vs}$   | W  | 0  |
| Heat dissipation capacity                                | $P_{diss}$ | W  | 0  |
| Operating ambient temperature min.                       |            | °C | -25  |
| Operating ambient temperature max.                       |            | °C | 70   |
| IEC/EN 61439 design verification                         |            |    |  |
| 10.2 Strength of materials and parts                     |            |    |  |
| 10.2.2 Corrosion resistance                              |            |    | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures |            |    | Meets the product standard's requirements. |

|  |  |  |  |
|--|--|--|--|
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |  |  | Meets the product standard's requirements.   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |  |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |  |  | Please enquire   |
| 10.2.5 Lifting   |  |  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.2.6 Mechanical impact   |  |  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.2.7 Inscriptions  |  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES  |  |  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.4 Clearances and creepage distances   |  |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  |  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.6 Incorporation of switching devices and components   |  |  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.7 Internal electrical circuits and connections  |  |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  |  | Is the panel builder's responsibility.   |
| 10.9 Insulation properties   |  |  |  |
| 10.9.2 Power-frequency electric strength   |  |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material   |  |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  |  | Not applicable.  |
| 10.11 Short-circuit rating   |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.12 Electromagnetic compatibility  |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.13 Mechanical function  |  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Text plate for control circuit devices (EC000624)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss10.0.1-27-37-12-25 [AKF043014])

|                     |  |    |                 |
|---------------------|--|----|-----------------|
| Imprint             |  |    | Without imprint |
| Imprint ISO symbols |  |    | Without imprint |
| Colour              |  |    | Yellow          |
| Shape               |  |    | Round           |
| Width               |  | mm | 60              |
| Height              |  | mm | 60              |
| Outer diameter      |  | mm | 60              |

## Approvals

|                             |  |  |                                   |
|-----------------------------|--|--|-----------------------------------|
| North America Certification |  |  | UL/CSA certification not required |
|-----------------------------|--|--|-----------------------------------|

## Dimensions

