

## Miniature circuit breaker (MCB), 25 A, 1p, characteristic: K

**Part no.** FAZ-K25/1  
**278601**

**EL Number**  
**(Norway)** 1695318

Product name	Eaton Moeller series xEffect - FAZ MCB
Part no.	FAZ-K25/1
EAN	4015082786014
Product Length/Depth	80 millimetre
Product height	75.5 millimetre
Product width	17.7 millimetre
Product weight	0.115 kilogram
Compliances	UL CSA09 (with supplementary protector only) RoHS conform
Certifications	IEC/EN 60898 CE marking UL (File No. E177451) CSA (Class No. 3215-30) CSA (File No. 204453) CSA-C22.2 No. 235 IEC/EN 60947-2 UL (Category Control Number QVNU2, QVNU8) North America (UL recognized, CSA certified) UL 1077 EN45545-2 IEC 61373
Product Tradename	xEffect - FAZ
Product Type	MCB
Product Sub Type	None
Application	Branch circuits, not as BCPD Switchgear for industrial and advanced commercial applications xEffect - Switchgear for industrial and advanced commercial applications
Number of poles	Single-pole
Number of poles (total)	1
Number of poles (protected)	1
Tripping characteristic	K
Release characteristic	K
Amperage Rating	25 A
Type	FAZ Miniature circuit breaker
Voltage type	AC
Voltage rating	240 V AC
Voltage rating at DC	60 V DC (per pole)
Voltage rating (UL CSA 13)	277 V AC; 48 V DC
Rated operational voltage (Ue) - max	230 V
Rated insulation voltage (Ui)	440 V
Rated impulse withstand voltage (Uimp)	4 kV
Frequency rating - min	50 Hz
Frequency rating - max	60 Hz
Rated switching capacity (IEC/EN 60947-2)	10 kA
Operational switching capacity	7.5 kA
Rated short-circuit breaking capacity (EN 60898) at 230 V	0 kA
Rated short-circuit breaking capacity (EN 60898) at 400 V	0 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V	10 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 400 V	10 kA
Admissible back-up fuse - max	125 A gL/gG

Selectivity class		3
Lifespan, electrical		10000 operations
Overvoltage category		III
Pollution degree		2
Direction of incoming supply		As required
Frame		45 mm
Enclosure width		80 mm
Width in number of modular spacings		1
Built-in depth		70.5 mm
Mounting width per pole		17.5 mm
Mounting width		17.5 mm
Mounting Method		Top-hat rail IEC/EN 60715
Mounting position		As required
Degree of protection		IP40 (when fitted) IP20 (IEC) IP20 UL/CSA Type: -
Terminals (top and bottom)		Twin-purpose terminals
Connectable conductor cross section (solid-core) - min		1 mm <sup>2</sup>
Connectable conductor cross section (solid-core) - max		25 mm <sup>2</sup>
Connectable conductor cross section (multi-wired) - min		1 mm <sup>2</sup>
Connectable conductor cross section (multi-wired) - max		25 mm <sup>2</sup>
Terminal capacity of screw terminals for main cable		10 mm <sup>2</sup> (2x)
Terminal capacity (control cable)		25 mm <sup>2</sup> (1x)
Terminal protection		Finger and hand touch safe, DGUV VS3, EN 50274
Busbar material thickness		0.8 mm - 2 mm
Rated operational current for specified heat dissipation (I <sub>n</sub> )		25 A
Heat dissipation per pole, current-dependent		0 W
Equipment heat dissipation, current-dependent		2.6 W
Static heat dissipation, non-current-dependent		0 W
Heat dissipation capacity		0 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		75 °C
Current limiting class		3
Features		Additional equipment possible
Special features		Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
Used with		Miniature circuit breaker FAZ

## Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)		
Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss10.0.1-27-14-19-01 [AAB905014])		
Built-in depth	mm	70.5
Release characteristic		K
Number of poles (total)		1
Number of protected poles		1
Rated current	A	25
Rated voltage	V	230
Rated insulation voltage U <sub>i</sub>	V	440
Rated impulse withstand voltage U <sub>imp</sub>	kV	4
Rated short-circuit breaking capacity I <sub>cn</sub> according to EN 60898 at 230 V	kA	0
Voltage type		AC
Rated short-circuit breaking capacity I <sub>cn</sub> according to EN 60898 at 400 V	kA	0

Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V	kA	10
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V	kA	10
Frequency	Hz	50 - 60
Current limiting class		3
Flush-mounted installation		No
Concurrently switching neutral conductor		No
Over voltage category		3
Pollution degree		2
Additional equipment possible		Yes
Width in number of modular spacings		1
Degree of protection (IP)		IP20
Ambient temperature during operating	°C	-25 - 75
Connectable conductor cross section multi-wired	mm <sup>2</sup>	1 - 25
Connectable conductor cross section solid-core	mm <sup>2</sup>	1 - 25
Explosion-proof		No