

Product Technical Sheet

21 Feb 2022 18:52



417.32677

FLUSH-MOUNTING SOCKET

32A 3P+N+E 5h 600-690V 50Hz 60Hz
84X106MM Screw terminals

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|----------------------------|-----------------------|-----------------------------------|---|
| Commercial series | EUREKA Series | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Type of product | FLUSH-MOUNTING SOCKET | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | FLUSH-MOUNTING SOCKET | | |
| Mounting version | FLUSH MOUNTING | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated current | 32A | | |
| Poles | 3P+N+E | | |
| Hour position | 5h | | |
| Rated voltage (range) | 400V-up | | |
| Rated voltage | 600-690V | | |
| Working frequency | 50Hz | | |
| Working frequency | 60Hz | | |
| Colour | BLACK | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67 | | |
| Protection degree IK | IK07 | | |
| Types of available outlets | ANGLED | | |
| Terminals | Screw terminals | | |

| | |
|------------------|--------------|
| Contact material | CuZn (brass) |
| Flange | 84X106MM |