



## 422.16674

# FLUSH-MOUNTING SOCKET

16A 3P+N+E 3h 380V 50Hz / 440V 60Hz 50Hz  
60Hz 75X75MM Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	FLUSH-MOUNTING SOCKET	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Commercial series	EUREKA Series	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Synthetical description	FLUSH-MOUNTING SOCKET		
Mounting version	FLUSH MOUNTING	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Rated current	16A		
Poles	3P+N+E		
Hour position	3h		
Rated voltage (range)	250-400V		
Rated voltage	380V 50Hz / 440V 60Hz		
Working frequency	50Hz		
Working frequency	60Hz		
Colour	RED		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK09		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		

Contact material	CuZn (brass)
Flange	75X75MM