

# Product Technical Sheet

21 Feb 2022 19:14



## TECHDATA

Type of product

INTERLOCKED SOCKET

## STANDARDS AND LAWS

EN 60309-1 (1999) [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part

Commercial series	OMNIA Series	EN 60309-2 (1999)	1: General requirements
Synthetical description	INTERLOCKED SOCKET		[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability
Mounting version	SURFACE MOUNTING		requirements for pin and contact-tube accessories of harmonized configurations
Rated current	16A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poles	3P+E	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability
Hour position	9h		requirements for pin and contact-tube accessories of harmonized configurations
Rated voltage (range)	200-250V	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Rated voltage	200-250V		
Working frequency	60Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Working frequency	50Hz		
Colour	BLUE	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability
Material	THERMOPLASTIC		requirements for pin and contact-tube accessories of harmonized configurations
Protection degree	Splash proof	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Protection degree IP	IP44		
Protection degree IK	IK08	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Flange	136X125MM_PAR		
Options	With mechanical interlock		
Notes	WITHOUT FUSE HOLDER		