## **Product Technical Sheet**

21 Feb 2022 18:22





## **512.M16574**SURFACE MOUNTING SOCKET

16A 3P+N+E 3h 380V 50Hz / 440V 60Hz 50Hz 60Hz Screw terminals

**Product Approvals** 

TECHDATA		STANDARDS	S AND LAWS
Commercial series	OPTIMA Series	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Type of product	SURFACE MOUNTING SOCKET	and couplers for industrial purposes. Pa 2: Dimensional interchangeability requirements for pin and contact-tube	General requirements European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Synthetical description	SURFACE MOUNTING SOCKET		2: Dimensional interchangeability
Mounting version	SURFACE MOUNTING	DIRECTIVE LOW VOLTAGE 2014/35	[European Directives] Low Voltage Directive
Rated current	16A	/UE	
Poles	3P+N+E		
Hour position	3h		
Rated voltage (range)	250-400V		
Rated voltage	380V 50Hz / 440V 60Hz		
Working frequency	50Hz		
Working frequency	60Hz		
Colour	RED		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44/IP54		
Protection degree IK	IK08		
Types of available outlets	ANGLED		
Terminals	Screw terminals		

Contact material	CuZn (brass)	
Cable entry	M20X1,5	