



# 316.16466

## PROLONGADOR

16A 3P+T 7h 480-500V 50Hz 60Hz Bornes con tornillo

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	PROLONGADOR	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie comercial	Serie EUREKA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descripción	PROLONGADOR		
Tipo de instalación	PORTÁTIL		
Intensidad nominal	16A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Polos	3P+T		
Posición de hora	7h		
Tensión nominal (range)	400V-up		
Tensión nominal	480-500V		
Frecuencia nominal	60Hz		
Frecuencia nominal	50Hz		
Color	NEGRO		
Material	TERMOPLÁSTICO		
Grado de protección	Watertight		
Grado de protección IP	IP66/IP67		
Grado de protección IK	IK07		
Tipos de salidas disponibles	RECTA		
Bornes	Bornes con tornillo		

Material de los contactos	CuZn (latón)
Salida del cable	PRENSAESTOPAS