



422.16632

BASE EMPOTRABLE

16A 2P+T 2h >50V >300-500Hz 75X75MM
Bornes con tornillo

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|------------------------------|---------------------|-----------------------------------|---|
| Tipo de producto | BASE EMPOTRABLE | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Serie comercial | Serie EUREKA | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción | BASE EMPOTRABLE | | |
| Tipo de instalación | EMPOTRABLE | | |
| Intensidad nominal | 16A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Polos | 2P+T | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Posición de hora | 2h | | |
| Tensión nominal (range) | 50-200V | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Tensión nominal | >50V | | |
| Frecuencia nominal | >300-500Hz | | |
| Color | VERDE | | |
| Material | TERMOPLÁSTICO | | |
| Grado de protección | Splash proof | | |
| Grado de protección IP | IP44 | | |
| Grado de protección IK | IK09 | | |
| Tipos de salidas disponibles | RECTA | | |
| Bornes | Bornes con tornillo | | |
| Material de los contactos | CuZn (latón) | | |

Brida de fijación

75X75MM