



422.16664

BASE EMPOTRABLE

16A 3P+T 3h 380V 50Hz / 440V 60Hz 50Hz
60Hz 75X75MM Bornes con tornillo

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|------------------------------|-----------------------|-----------------------------------|---|
| Serie comercial | Serie EUREKA | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Tipo de producto | BASE EMPOTRABLE | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción | BASE EMPOTRABLE | | |
| Tipo de instalación | EMPOTRABLE | | |
| Intensidad nominal | 16A | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Polos | 3P+T | | |
| Posición de hora | 3h | | |
| Tensión nominal (range) | 250-400V | | |
| Tensión nominal | 380V 50Hz / 440V 60Hz | | |
| Frecuencia nominal | 60Hz | | |
| Frecuencia nominal | 50Hz | | |
| Color | ROJO | | |
| Material | TERMOPLÁSTICO | | |
| Grado de protección | Splash proof | | |
| Grado de protección IP | IP44 | | |
| Grado de protección IK | IK09 | | |
| Tipos de salidas disponibles | RECTA | | |
| Bornes | Bornes con tornillo | | |

| | |
|---------------------------|--------------|
| Material de los contactos | CuZn (latón) |
| Brida de fijación | 75X75MM |