

# 500.M16874

## BASE ENCLAV. MEC.

16A 3P+N+T 3h 380V 50Hz / 440V 60Hz 50Hz  
60Hz 136X125MM\_PAR Bornes con tornillo Con  
enclavamiento mecánico



Product Approvals

| TECHDATA                  |                       | STANDARDS AND LAWS                |   |
|---------------------------|-----------------------|-----------------------------------|---|
| Tipo de producto          | BASE ENCLAV. MEC.     | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Serie comercial           | Serie OMNIA           | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción               | BASE ENCLAV. MEC.     |                                   |   |
| Tipo de instalación       | MURAL                 |                                   |   |
| Intensidad nominal        | 16A                   | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Polos                     | 3P+N+T                | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Posición de hora          | 3h                    |                                   |   |
| Tensión nominal (range)   | 250-400V              | EN 60309-4 (2007)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock   |
| Tensión nominal           | 380V 50Hz / 440V 60Hz |                                   |   |
| Frecuencia nominal        | 50Hz                  | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Frecuencia nominal        | 60Hz                  | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Color                     | ROJO                  |                                   |   |
| Material                  | TERMOPLÁSTICO         |                                   |   |
| Grado de protección       | Splash proof          | EN 60309-4/A1 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock   |
| Grado de protección IP    | IP44                  |                                   |   |
| Grado de protección IK    | IK08                  | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Bornes                    | Bornes con tornillo   |                                   |   |
| Material de los contactos | CuZn (latón)          |                                   |   |

|                   |                            |
|-------------------|----------------------------|
| Brida de fijación | 136X125MM_PAR              |
| Opciones          | Con enclavamiento mecánico |
| Notas             | SIN PORTAFUSIBLES          |