

# 500.M3287

## BASE ENCLAV. MEC.

32A 3P+N+T 6h 346-415V 50Hz 60Hz  
136X125MM\_PAR Bornes con tornillo Con  
enclavamiento mecánico



Product Approvals

| TECHDATA                  |                     | STANDARDS AND LAWS                |   |
|---------------------------|---------------------|-----------------------------------|---|
| Tipo de producto          | BASE ENCLAV. MEC.   | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Serie comercial           | Serie OMNIA         | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción               | BASE ENCLAV. MEC.   | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Tipo de instalación       | MURAL               | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Intensidad nominal        | 32A                 | EN 60309-4 (2007)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock   |
| Polos                     | 3P+N+T              | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Posición de hora          | 6h                  | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Tensión nominal (range)   | 250-400V            | EN 60309-4/A1 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock   |
| Tensión nominal           | 346-415V            | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Frecuencia nominal        | 60Hz                |                                   |   |
| Frecuencia nominal        | 50Hz                |                                   |   |
| Color                     | ROJO                |                                   |   |
| Material                  | TERMOPLÁSTICO       |                                   |   |
| Grado de protección       | Splash proof        |                                   |   |
| Grado de protección IP    | IP44                |                                   |   |
| Grado de protección IK    | IK08                |                                   |   |
| Bornes                    | Bornes con tornillo |                                   |   |
| Material de los contactos | CuZn (latón)        |                                   |   |

|                   |                            |
|-------------------|----------------------------|
| Brida de fijación | 136X125MM_PAR              |
| Opciones          | Con enclavamiento mecánico |
| Notas             | SIN PORTAFUSIBLES          |