



505.M1675

BASE ENCLAV. MEC.

16A 3P+N+T 9h 208-250V 50Hz 60Hz
136X125MM_PAR Bornes con tornillo Con
enclavamiento mecánico

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|---------------------------|---------------------|-----------------------------------|---|
| Serie comercial | Serie OMNIA | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Tipo de producto | BASE ENCLAV. MEC. | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción | BASE ENCLAV. MEC. | | |
| Tipo de instalación | MURAL | | |
| Intensidad nominal | 16A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Polos | 3P+N+T | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Posición de hora | 9h | | |
| Tensión nominal (range) | 200-250V | EN 60309-4 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock |
| Tensión nominal | 208-250V | | |
| Frecuencia nominal | 60Hz | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Frecuencia nominal | 50Hz | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Color | AZUL | | |
| Material | TERMOPLÁSTICO | | |
| Grado de protección | Watertight | EN 60309-4/A1 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock |
| Grado de protección IP | IP66/IP67 | | |
| Grado de protección IK | IK08 | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Bornes | Bornes con tornillo | | |
| Material de los contactos | CuZn (latón) | | |

| | |
|-------------------|----------------------------|
| Brida de fijación | 136X125MM_PAR |
| Opciones | Con enclavamiento mecánico |
| Notas | SIN PORTAFUSIBLES |