

Product Technical Sheet

21 feb 2022 18:00



512.16561

BASE MURAL

16A 3P+T 10h >50V 100-300Hz Bornes con tornillo

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	BASE MURAL	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie comercial	Serie OPTIMA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descripción	BASE MURAL		
Tipo de instalación	MURAL		
Intensidad nominal	16A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Polos	3P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Posición de hora	10h		
Tensión nominal (range)	50-200V	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tensión nominal	>50V		
Frecuencia nominal	100-300Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Color	VERDE		
Material	TERMOPLÁSTICO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Grado de protección	Splash proof		
Grado de protección IP	IP44/IP54		
Grado de protección IK	IK08		
Tipos de salidas disponibles	INCLINADA		
Bornes	Bornes con tornillo		
Material de los contactos	CuZn (latón)		