



590.GE16004

INTERRUPTOR DE MANIOBRA

160A 4P IP55 380x300x120mm IK08 GENERAL GRIS/NEGRO GW 650°C

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	INTERRUPTOR DE MANIOBRA	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Serie comercial	Serie ISOLATORS-TP	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descripción	INTERRUPTOR DE MANIOBRA	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	POLÍMERO TÉCNICO	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Grado de protección IP	IP55	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tipo	GENERAL	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Color	GRIS/NEGRO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Intensidad nominal	160A		
Polos	4P		
Dimensiones	380x300x120mm		
Prueba del hilo incandescente	GW 650°C		
Grado de protección IK	IK08		