



# 211.1630.TR

## SPINA MOBILE

16A 2P+T 4h 100-130V 50Hz 60Hz Morsetti a vite

Certificati

TECHDATA		NORME E LEGGI	
Tipologia prodotto	SPINA MOBILE	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie commerciale	Serie EUREKA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	SPINA MOBILE		
Tipo installazione	PORTATILE		
Corrente nominale	16A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Poli	2P+T		
Riferimento Orario	4h		
Tensione nominale (range)	50-200V		
Tensione nominale	100-130V		
Frequenza d'impiego	60Hz		
Frequenza d'impiego	50Hz		
Colore	GIALLO		
Materiale	TERMOPLASTICO		
Grado di protezione generico	Protetto da getti d'acqua		
Grado di protezione IP	IP44		
Grado di protezione IK	IK07		
Tipo di uscite disponibili	DIRITTA		
Morsetti	Morsetti a vite		

Materiale di contatto	CuZn (ottone)
Trattamento superficiale cont.	Nichelato
Uscita cavo	PASSACAVO
Note	IMPUGNATURA TRASPARENTE